



	REACH	CTL® GmbH	CEN TEX BEL	
--	-------	-----------	-------------------	--





This new article Fusion is part of our Comfort Collection. This heavy jacquard woven quality, is a valuable addition to this collection of soft and elegant fabrics, all rich in volume.

Developed by our dedicated team as a fabric that will lift the appearance of any furniture item on its own. The dessin is subtle and can be styled both as an interior basis or accent fabric. For example, in combination with other Textaafoam fabrics such as Challenger, Shout or Leaf.

Fusion offers a heavy and chunky quality while the chenille yarns create an elegant, soft and full hand feel. This fabric is perfect for both loose covers and tight fitted upholstery.

To create the voluminous and luxury appearance we used heavy chenille yarns. Typically, seat depression and shading are possible. With loving care during use this can be minimalized. This article is washable at 30 degrees Celsius.

* Please wash the cover inside out. We also recommend to put the fabric back on the furniture slightly damp after washing to ensure it dries evenly.

Textaafoam ^{originals} Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ Faceside 100%PES / Chenille jaquard

Suitable for

Sofa's, beds, chairs with fitted and loose fitting upholstery



graphite 66

niagara 158

indigo 90



teal 198



thyme 206

army 14







cognac 28

mustard 06

brandy 127



copper 126

blush 92



carmine 36



pale 200

		1		
Fusion - Article passport				
A voluminous jacquard woven quality with	heavy chenille yarns creates a soft, elegant and full ha	and feel.		
Available from stock in a wide range of cor	ntemporary and commercial colours.			
Product characteristics				
Productgroup	chenille jaquard			
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery			
Composition faceside	100%PES			
Statistic Code	58013600			
Coating	SBR			
Dyeing method	piece dyed			
Available colours	19			

Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09			
				DRY	WET	DGM	DGM+				
Abrasion Resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	85.000		min. 8.000	min. 16.000	А			
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	А			
Colour fastness to light	DIN EN ISO 105-B02:2014-11. Process 3, exposure level 5										
	light colours	CTL	grade	5		min. 4	min. 5	А			
	middle colours	CTL	grade	5		min. 4	min. 5	А			
	dark colours	CTL	grade	5		min. 4	min. 5	А			
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11	DIN EN ISO 105-X12:2016-11									
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A			
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A			
	dark colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A			
Ignatability	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) Regulations: 1988 No. 1324. Schedule 4 part I. Ignition source 0. cigarette	CTL		passed							

Processing specifications								
Minimum workable width in centimeters	± 138							
Roll length in meters	± 30							
Material weight in grams per linear meter	± 580							
Test	Test Specification	Executed by laboratory:			esult Norm RAL GZ 430/4:2016-01			Norm DIN EN 14 465:2006-09
				WARP	WEFT	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.124	1.139	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	85,9	70,6	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,0	2,0	max. 5	max. 4	A/A
Chemical substances	REACH	Centexbel		pass	sed			

Cleaning specifications Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				WARP	WEFT	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN ENISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	- 0,4	+ 0,0	n/a	n/a	A/A
P 🐨 🖄 🗟 🗟	We recommend to immediately place the cover back to the piece of furniture slightly damp after washing.							CTL [®] GmbH



Textaafoam b.v.

La Défense 11 | 5026 SC Tilburg P.O. Box 12 | 5050 AA Goirle The Netherlands

T +31(0)13 534 5934 F +31(0)13 534 7586 E info@textaafoam.nl www.textaafoam.nl